



Commercial Product Line

CONTENTS

American Tradition™ 9000 Series 9200 - 2 $\frac{3}{8}$ " thick / 0.081 Tested U-Factor 9600 - 2" thick / 0.096 Tested U-Factor	p 2-5
Commercial Aluminum Series CA-320 - 1 $\frac{3}{4}$ " thick CA-315 - 1 $\frac{3}{4}$ " thick CA-110 - 1 $\frac{3}{4}$ " thick	p 6-9
5000 Series 5800 - 3" thick / 0.089 Tested U-Factor 5200 - 2" thick / 0.110 Tested U-Factor 5700 - 1 $\frac{3}{4}$ " thick / 0.097 Tested U-Factor	p 10-13
800 Series 3" thick / 0.089 Tested U-Factor	p 14-17
2000 Series 2" thick / 0.094 Tested U-Factor	p 18-21
700 Series 1 $\frac{3}{4}$ " thick / 0.093 Tested U-Factor	p 22-25
600 Series 1 $\frac{3}{8}$ " thick / 0.106 Tested U-Factor	p 26-29
Commercial Ribbed Steel 2" thick / Optional Insulation	p 30-33
Insulated Product Details	p 34-35
Thermal Performance U-Factor	p 36-37
Warranty Information	p 38
Glass Options	p 39
SelectView Options	p 40-41
Window Options	p 42-45
Color Options	p 45-47
Quality & Environmental Commitment	p 48-49



All U-Factors shown are based on testing solid doors. Adding lites will affect the tested U-Factor.

More info on page 36-37.



Create your garage door, view it on your building and receive a quote at **haascreate.com**.

Quality People. Quality Products.



We value our customers and manufacture our garage doors with the highest quality workmanship and raw materials.

Our method is simple. We hire quality people driven to produce quality products. We don't just say it - we do it. Together, we find innovative ways to solve problems and continuously improve while working smarter and safer. Our people take pride in their work and strive to provide the highest quality of product and service day in and day out. That's the Haas Door Difference.

As you read forward, allow us to open a door to endless possibilities for you!


haasdoor.com





9622 in sandstone

COMMERCIAL 9000 SERIES

2⁵/₈" or 2" Thick 

9200 - 2" base door & 5/8" overlay
9600 - 1 3/8" base door & 5/8" overlay



9000 Timeless Beauty.

We've taken the elegance of the original handcrafted wooden carriage house doors and the detail of the wrought iron hardware to produce a classic style made with modern technology and materials. Backed by a Lifetime Limited Warranty, American Tradition™ 9000 series doors are the ideal choice to add the classic look of a genuine carriage house door.

INSULATED



2

9240 in gray



9640 in brown

9000 Series / 2⁵/₈" thick or 2" thick / 0.081 or 0.096 Tested U-Factor

Single Door Designs



Double Door Designs



Solid Base & Overlay Colors




Wood Grain Base & Overlay Colors



All color combinations are available to mix and match base and overlay colors. Due to the printing process, colors may vary. For an accurate color match, contact your Haas Door dealer.

9000 QUICK GUIDE

Model	Door Thickness	Tested U-Factor	Max. Door Size		Section Skins	
			Width	Height	Inside	Outside
✓ 9200 models	2 ⁵ / ₈ " (66.7mm)	0.081	20'-2"	16'-0"	26 GA V-Groove Woodgrain Steel	26 GA Flush Woodgrain Steel
✓ 9600 models	2" (50.8mm)	0.096	18'-2"	16'-0"	26 GA V-Groove Woodgrain Steel	26 GA Flush Woodgrain Steel



A **Full Thermal Break** is used in the tongue-and-groove construction of all 9000 series doors. This rigid vinyl extrusion seals the joints and eliminates metal-to-metal contact, which limits the transfer of temperature.

9200 and 9600 series doors exceed the ASHRAE 90.1 Standard when installed with standard bottom seal and commonly available rigid/flexible vinyl door stop. 9200 includes air infiltration bulb seal between sections.

Window Designs

Windows available in top 2 sections



Glass Options


Insulated - 1/2" tempered (optional)



Non-Insulated - 1/8" tempered (standard)



Impact Polycarbonate - (UV rating on Clear only)



OPTIONS 9000 Series Available Options

- 2" or 3" Track
- Exhaust Port(s)
- Cam Safety Device
- Spring Bumpers
- Chain Hoist Operators
- High Cycle Springs
- Glazing (lites)
- High Cycle Rollers
- Keyed Lock
- Wind Load & Impact



For detailed information about the construction of this series, see pages 34-35.

* Glazed Arch multi-pane window options are not available in the following sizes:
9'-8" through 10'-7"
14'-0" through 15'-7"
18'-4" through 20'-2"



CA-320 in oregon douglas

COMMERCIAL ALUMINUM SERIES

1 3/4" Thick

CA-320 / CA-315 / CA-110



CA Clean Lines.

Haas CA-320, CA-315 and CA-110 Aluminum Sectional Doors are strong, durable, and elegant. A versatile product combining aluminum rails and stiles provides a strong-profiled frame structure with aluminum panels and a wide range of glazing choices. This is the ideal application for service stations, quick lube facilities, automobile dealerships, restaurants and other business where strength, appearance and corrosion resistance are key factors.



CA-320 in black anodized




CA-110 in black anodized

Commercial Aluminum / 1 3/4" thick



Insulated Option



For the highest thermal performance, select model CA-320ix with insulated rails and stiles. Tested U-Factor available upon request.

CA-110 Narrow Line Frame

The CA-110 and CA-110i sections are assembled using .045" minimum aluminum alloy tubular type extrusions with thru-bolt construction. Sections are 1-3/4" thick. Any Section height is available. Bottom rails are 3" on doors up to 13'-2" wide. Doors greater than 13'-2" wide have 4" bottom rails. Top and bottom rails are upgradeable to 4" or 6".



CA-110i at 8'3" wide and wider and CA-110 at 12'3" and wider, have built-in struts on each section. Dependent on the width size, E struts or cap struts may be included. All aluminum is clear anodized as standard. Panels for solid sections are .040" stucco embossed or .050" smooth aluminum. A wide variety of glazing materials are available.

Commerical Aluminum QUICK GUIDE

Model	Glazing Thickness	Max. Door Size		Max Area	Top Rail	Center Stile	Meeting Rail	Bottom Rail	Color Options	Section Joint	Panel & Glazing Types
		Width	Height								
CA-110	1/8"	16'-2"	14'-0"	226 Sq Ft	3" Standard; Upgradeable to 4" or 6"	1"	2"	3" Standard up to 13' 2" wide; then 4" Standard; Upgradeable to 4" or 6"	Clear Anodized, Black Anodized, Dark Bronze Anodized & Polar White	Shiplap	Polystyrene & Aluminum Laminated Panels
CA-110i *	1/4" & 1/2"	12'-2"	10'-0"	102 Sq Ft				3" Standard Upgradeable to 4" or 6"			Various Types & Thicknesses of Glazing
CA-315	1/8"	16'-2"	16'-0"	258 Sq Ft	4" Standard; Upgradeable to 6"	1"	4"	4" Standard Upgradeable to 6"	Anodized & Painted Colors (no Wood Grains)	Tongue & Groove with Bulb Seal meets IECC air infiltration reqmts	Polystyrene & Aluminum Laminated Panels
CA-315i *	1/4" & 1/2"										Various Types & Thicknesses of Glazing
CA-320	1/8"	28'-2"	20'-0"	500 Sq Ft	4" Standard up to 16'2" wide; then 6" Standard; Upgradeable to 6"	2"	4"	4" Standard up to 16' 2" wide; then 6" Standard; Upgradeable to 6"	All Colors	Tongue & Groove with Bulb Seal meets IECC air infiltration reqmts	Polystyrene & Aluminum Laminated Panels
CA-320i *	1/4" & 1/2"	20'-2"	16'-0"								Various Types & Thicknesses of Glazing
CA-320ix **											Various Types & Thicknesses of Glazing
CA-320i Impact*	1/4"	16'-2"	16'-0"		258 Sq Ft	6" Standard		6" Standard			Various Glazings, No Solid Panels

* - The i on the series name indicates it is a heavier glass/glazing option - 1/4" or 1/2".

** - The x on the series name indicates rails and stiles are insulated with polystyrene.

OPTIONS CA Available Options

- 2" or 3" Track
- Exhaust Port(s)
- Cam Safety Device
- Spring Bumpers
- High Cycle Springs
- Insulated Rails and Stiles (320ix only)
- Pass Door (320 & 320i only)
- High Cycle Rollers
- Chain Hoist
- Operators
- Top Header Seal
- Car Wash Cutout

Pass Door (exterior view)



Optional Exhaust Port (interior view)



(Only available on CA-320/CA-320i in all colors options, except wood grains. Door trim color is only available in clear anodized. Convenience only, not a legal exit, or ADA compliant.)

CA-315 Larger Glass with Heavy Duty Outer Frame

The CA-315 & CA-315i sections are assembled using .045" minimum aluminum alloy tubular type extrusions with thru-bolt construction. Sections are 1-3/4" thick. Any section height is available. Tongue & Groove section joints with bulb seal meets IECC Air Infiltration requirements. Bottom rails, top rails, and end stiles are 4". Top and bottom rails are upgradeable to 6".



CA-315i at 8'3" and CA-315 at 12'3" and wider, have built-in struts on each section. Dependent on the width size, E struts or cap struts may be included. All aluminum is clear anodized as standard. Panels for solid sections are .040" stucco embossed or .050" smooth aluminum. A wide variety of glazing materials are available.

CA-320 Heavy Duty Frame

CA-320, CA-320i and CA-320ix sections are assembled using .045" minimum aluminum alloy tubular type extrusions with thru-bolt construction. Sections are 1-3/4" thick. Any section height is available. Tongue & Groove section joints with bulb seal meets IECC Air Infiltration requirements. Bottom rails, top rails, and end stiles are 4" up to 16'2" wide, then change to 6". Top and bottom rails are upgradeable to 6".



CA-320i at 8'3" and wider, and the CA-320 at 12'3" and wider, have built-in struts on each section. Dependent on the width, E struts, cap struts, and support braces may be included. All aluminum is clear anodized as standard. Panels for solid sections are .040" stucco embossed or .050" smooth aluminum. A wide variety of glazing materials are available. Optional insulated rails and stiles add thermal performance.

COLOR OPTIONS

Standard Anodized Colors

- Clear Anodized
- Dark Bronze Anodized
- Black Anodized

Powder Coated Wood Grain Colors

- Oregon Douglas
- National Oak
- American Douglas
- Knotty Pine

Solid Painted Colors

- Polar White
- Almond
- Sahara Tan
- Sandstone
- Espresso
- Brown
- Painted Bronze
- Gray
- Charcoal
- Painted Black

- Colony Maple
- European Cherry
- Antique Cherry
- Heritage Maple
- Coffee
- Cherry with Flame
- National Cherry
- Spiced Walnut
- Black Walnut

Custom-matched color and powder coating are also available. Matching solid panels also available for all colors. Not all colors are available for all models, see Quick Guide on page 8. Due to the printing process, colors may vary. For an accurate color match, contact your Haas Door dealer.

Commercial Aluminum / 1 3/4" thick



5816 in polar white with large TL lites



5214 in polar white with full view lites



5780 in polar white

COMMERCIAL 5000 SERIES

3", 2" or 1 3/4" Thick



- 5814 / 5816 / 5870 / 5880
- 5210 / 5212 / 5214 / 5216 / 5267 / 5268 /
- 5270 / 5278 / 5280 / 5287
- 5710 / 5712 / 5714 / 5716 / 5767 / 5768 /
- 5770 / 5778 / 5780 / 5787



Natural Advantages for Unique Performance.

Haas Door Commercial Insulated Aluminum 5000 Series uses the natural advantages of aluminum and takes it to the next level. The Commercial 5000 Series has insulated garage doors with 24 gauge, corrosion-resistant aluminum that stands up in harsh weather conditions. In addition, the Commercial 5000 Series is available with wind load and impact options for severe weather prone areas such as high-velocity hurricane zones.

INSULATED




5816 in polar white




5216 in polar white

DOOR PANELS




Flush Stucco

Polar White
Model 5814 Window Options: p 45
Model 5210 Window Options: p 42-45
Model 5214 Window Options: p 45
Model 5710 Window Options: p 42-45
Model 5714 Window Options: p 45



V-Groove Stucco

Polar White
Model 5816 Window Options: p 45
Model 5212 Window Options: p 44-45
Model 5216 Window Options: p 45
Model 5712 Window Options: p 44-45
Model 5716 Window Options: p 45



Raised Ranch Stucco Panel

Polar White
Model 5870 No window options available.
Model 5270 Window Options: p 44
Model 5770 Window Options: p 44
Model 5267 Window Options: p 43
Model 5767 Window Options: p 43
Model 5287 Window Options: p 42
Model 5787 Window Options: p 42



Raised Standard Stucco Panel

Polar White
Model 5880 No window options available.
Model 5280 Window Options: p 42
Model 5780 Window Options: p 42
Model 5268 Window Options: p 43
Model 5768 Window Options: p 43
Model 5278 Window Options: p 44
Model 5778 Window Options: p 44

Model	Door Thickness	Tested U-Factor	Max. Door Size		End Stile Type	Section Skins	
			Width	Height		Inside	Outside
5814	3" (76.2mm)	0.089	21'-2"	28'-0"	16 GA Steel	24 GA V-Groove Stucco Aluminum	24 GA Flush Stucco Aluminum
5816	3" (76.2mm)	0.089	21'-2"	28'-0"	16 GA Steel	24 GA V-Groove Stucco Aluminum	24 GA V-Groove Stucco Aluminum
5870	3" (76.2mm)	0.089	21'-2"	28'-0"	16 GA Steel	24 GA V-Groove Stucco Aluminum	24 GA Ranch Panel Stucco Aluminum
5880	3" (76.2mm)	0.089	21'-2"	28'-0"	16 GA Steel	24 GA V-Groove Stucco Aluminum	24 GA Standard Panel Stucco Aluminum
5210	2" (50.8mm)	0.110	18'-2"	16'-0"	Extruded End Cap	24 GA V-Groove Stucco Aluminum	24 GA Flush Stucco Aluminum
5212	2" (50.8mm)	0.110	18'-2"	16'-0"	Extruded End Cap	24 GA V-Groove Stucco Aluminum	24 GA V-Groove Stucco Aluminum
5214	2" (50.8mm)	0.110	21'-2"	28'-0"	16 GA Steel	24 GA V-Groove Stucco Aluminum	24 GA Flush Stucco Aluminum
5216	2" (50.8mm)	0.110	21'-2"	28'-0"	16 GA Steel	24 GA V-Groove Stucco Aluminum	24 GA V-Groove Stucco Aluminum
5267, 5270, 5287	2" (50.8mm)	0.110	21'-2"	28'-0"	Extruded End Cap	24 GA V-Groove Stucco Aluminum	24 GA Ranch Panel Stucco Aluminum
5268, 5278, 5280	2" (50.8mm)	0.110	21'-2"	28'-0"	Extruded End Cap	24 GA V-Groove Stucco Aluminum	24 GA Standard Panel Stucco Aluminum
5710	1-3/4" (44.5mm)	0.097	18'-2"	16'-0"	Extruded End Cap	24 GA V-Groove Stucco Aluminum	24 GA Flush Stucco Aluminum
5712	1-3/4" (44.5mm)	0.097	18'-2"	16'-0"	Extruded End Cap	24 GA V-Groove Stucco Aluminum	24 GA V-Groove Stucco Aluminum
5714	1-3/4" (44.5mm)	0.097	21'-2"	28'-0"	16 GA Steel	24 GA V-Groove Stucco Aluminum	24 GA Flush Stucco Aluminum
5716	1-3/4" (44.5mm)	0.097	21'-2"	28'-0"	16 GA Steel	24 GA V-Groove Stucco Aluminum	24 GA V-Groove Stucco Aluminum
5767, 5770, 5787	1-3/4" (44.5mm)	0.097	21'-2"	28'-0"	Extruded End Cap	24 GA V-Groove Stucco Aluminum	24 GA Ranch Panel Stucco Aluminum
5768, 5778, 5780	1-3/4" (44.5mm)	0.097	21'-2"	28'-0"	Extruded End Cap	24 GA V-Groove Stucco Aluminum	24 GA Standard Panel Stucco Aluminum

OPTIONS

5000 Series Available Options


- 2" or 3" Track
- Double Steel End Stiles
- Exhaust Port
- Cam Safety Device
- Spring Bumpers
- Chain Hoist
- Operators
- Top Header Seal
- Keyed Lock (5200 & 5700)
- Aluminum Full View Section (5200 & 5700)
- High Cycle Springs
- High Cycle Rollers
- Wind Load & Impact
- ASTM E 84 Fire Rated



Optional Exhaust Port (interior view)




5800 Series



A **Full Thermal Break** is used in the tongue-and-groove construction of all 5800 series doors. This rigid vinyl extrusion seals the joints and eliminates metal-to-metal contact, which limits the transfer of temperature.

5800 series doors include **Air Infiltration Seals**, which exceed the ASHRAE 90.1 Standard when installed with standard bottom seal and commonly available rigid/flexible vinyl door stop.


5200 Series



A **Full Thermal Break** is used in the tongue-and-groove construction of all 5200 series doors. This rigid vinyl extrusion seals the joints and eliminates metal-to-metal contact, which limits the transfer of temperature.

5200 series doors include **Air Infiltration Seals**, which exceed the ASHRAE 90.1 Standard when installed with standard bottom seal and commonly available rigid/flexible vinyl door stop.

5700 Series



A **Full Thermal Break** is used in the tongue-and-groove construction of all 5700 series doors. This rigid vinyl extrusion seals the joints and eliminates metal-to-metal contact, which limits the transfer of temperature.

For detailed information about the construction of this series, see pages 34-35.



816 in carbon black with large TL lites

COMMERCIAL 800 SERIES

3" Thick



814 / 816 / 832 / 833 / 832-20 /
833-20 / 870 / 880 / 890



The Architects' Choice For the Most Demanding Specifications

The outstanding features and benefits of the Haas 800 Series have made it the door of choice among commercial and industrial architects. The 800 series commercial insulated steel doors feature a full 3" pressure-injected core of high-density environmentally compliant polyurethane foam insulation with a tested U-Factor of 0.089 – the best in the commercial door industry. The 800 series is exceptionally strong and is reinforced with roll-formed galvanized steel struts and double-end hinges as required to meet or exceed local wind load specifications. It is the ideal door for locations that require both maximum energy efficiency and durable strength.



816 in bronze with large TL lites




816 in polar white with large TL lites


INSULATED SYSTEMS




DOOR PANELS




Flush Woodgrain
All colors except Graywood and Bi-Directional Wood Grain colors
Model 814 Window Options: p 45




V-Groove Woodgrain
All colors except Graywood and Bi-Directional Wood Grain colors
Model 816 Window Options: p 45



Flush Smooth
Polar White and Brown
Model 832 Window Options: p 41
Model 832-20 Window Options: p 45



V-Groove Smooth
Polar White and Brown
Model 833 Window Options: p 45
Model 833-20 Window Options: p 45




Raised Ranch Woodgrain Panel
All Colors except Graywood and Bi-Directional American Walnut
Model 870
No window options available.



Raised Standard Woodgrain Panel
All Colors except Graywood and Bi-Directional American Walnut
Model 880
No window options available.



Raised Sculptured Woodgrain Panel
All Colors except Graywood and Bi-Directional American Walnut
Model 890
No window options available.



A **Full Thermal Break** is used in the tongue-and-groove construction of all 800 series doors. This rigid vinyl extrusion seals the joints and eliminates metal-to-metal contact, which limits the transfer of temperature.

800 series doors include **Air Infiltration Seals**, which exceed the ASHRAE 90.1 Standard when installed with standard bottom seal and commonly available rigid/flexible vinyl door stop.

800 QUICK GUIDE

Model	Door Thickness	Tested U-Factor*	Max. Door Size		End Stile Type	Section Skins	
			Width	Height		Inside	Outside
✓ 814	3" (76.2mm)	0.089	38'-2"	32'-0"	16 GA Steel	26 GA V-Groove Woodgrain Steel	26 GA Flush Woodgrain Steel
✓ 816	3" (76.2mm)	0.089	38'-2"	32'-0"	16 GA Steel	26 GA V-Groove Woodgrain Steel	26 GA V-Groove Woodgrain Steel
✓ 832	3" (76.2mm)	.0.089	24'-2"	32'-0"	16 GA Steel	26 GA V-Groove Woodgrain Steel	20 GA Flush Smooth Steel
✓ 833	3" (76.2mm)	.0.089	38'-2"	32'-0"	16 GA Steel	26 GA V-Groove Woodgrain Steel	20 GA V-Groove Smooth Steel
✓ 832-20	3" (76.2mm)	0.089	24'-2"	32'-0"	16 GA Steel	20 GA V-Groove Smooth Steel	20 GA Flush Smooth Steel
✓ 833-20	3" (76.2mm)	0.089	38'-2"	32'-0"	16 GA Steel	20 GA V-Groove Smooth Steel	20 GA V-Groove Smooth Steel
✓ 870	3" (76.2mm)	0.089	24'-0"	32'-0"	16 GA Steel	26 GA V-Groove Woodgrain Steel	26 GA Ranch Panel Woodgrain Steel
✓ 880	3" (76.2mm)	0.089	24'-0"	32'-0"	16 GA Steel	26 GA V-Groove Woodgrain Steel	26 GA Standard Panel Woodgrain Steel
✓ 890	3" (76.2mm)	0.089	24'-0"	32'-0"	16 GA Steel	26 GA V-Groove Woodgrain Steel	26 GA Sculptured Panel Woodgrain Steel

OPTIONS

800 Series Available Options

- 2" or 3" Track
- Double Steel End Stiles
- Exhaust Port
- Cam Safety Device
- Spring Bumpers
- Chain Hoist
- Operators
- High Cycle Springs
- Glazing (lites)
- High Cycle Rollers
- Wind Load & Impact
- ASTM E 84 Fire Rated

Optional Exhaust Port (interior view)



For detailed information about the construction of this series, see pages 34-35.



2016 in bronze with full view lites

COMMERCIAL 2000 SERIES

2" Thick



2010 / 2012 / 2014 / 2016 / 2032 /
2033 / 2032-20 / 2033-20 / 2060 /
2061 / 2063 / 2064 / 2067 / 2068 /
2069 / 2070 / 2071 / 2072 / 2073 /
2074 / 2078 / 2079 / 2080 / 2081 /
2082 / 2087 / 2090



2000 Series / 2" thick / 0.094 Tested U-Factor

2000

The Strength To Keep Out Noise and Weather

Haas 2000 Series commercial insulated steel doors are manufactured with the elements in mind. They will enhance the beauty of your building while insulating and dampening outside noise at the same time. Choosing low U-Factor sectional doors will help increase energy efficiency and savings. Polyurethane insulation provides the lowest U-Factor available in sectional steel doors.

2000 series doors are reinforced with roll-formed galvanized steel struts and double-end hinges, as required to meet wind load specifications and to comply with ANSI/DASMA 102-2004. The protective coating system is found on both the interior and exterior steel.



2080 in white with standard plain lites



2016 in brown with pass door




2032 in polar white with large TL lites


DOOR PANELS




Flush Woodgrain
All colors except Bi-Directionals
Model 2010 Window Options: p 42-45
Model 2014 Window Options: p 45



V-Groove Woodgrain
All colors except Bi-Directionals
Model 2012 Window Options: p 44-45
Model 2016 Window Options: p 45




Flush Smooth
Polar White and Brown
Model 2032 Window Options: p 45
Model 2032-20 Window Options: p 45




V-Groove Smooth
Polar White and Brown
Model 2033 Window Options: p 45
Model 2033-20 Window Options: p 45




Ribbed Short Woodgrain Panel
All colors except Bi-Directional
American Walnut for 2072 and 2082
Model 2060 Window Options: p 43
Model 2072 Window Options: p 44
Model 2082 Window Options: p 42




Recessed Short Woodgrain Panel
All colors except Bi-Directional
American Walnut for 2071 and 2081
Model 2061 Window Options: p 43
Model 2071 Window Options: p 44
Model 2081 Window Options: p 42



Recessed Long Woodgrain Panel
All colors except Bi-Directional
American Walnut for 2073
Model 2063 Window Options: p 43
Model 2073 Window Options: p 44



Ribbed Long Woodgrain Panel
All colors except Bi-Directional
American Walnut for 2074
Model 2064 Window Options: p 43
Model 2074 Window Options: p 44




Raised Ranch Woodgrain Panel
All colors except Bi-Directional
American Walnut
Model 2070 Window Options: p 44
Model 2067 Window Options: p 43
Model 2087 Window Options: p 42



Raised Standard Woodgrain Panel
All colors except Bi-Directional
American Walnut
Model 2080 Window Options: p 42
Model 2068 Window Options: p 43
Model 2078 Window Options: p 44



Raised Sculptured Woodgrain Panel
All colors except Bi-Directional
American Walnut
Model 2090 Window Options: p 42
Model 2069 Window Options: p 43
Model 2079 Window Options: p 44



A **Full Thermal Break** is used in the tongue-and-groove construction of all 2000 series doors. This rigid vinyl extrusion seals the joints and eliminates metal-to-metal contact, which limits the transfer of temperature.

2000 series doors include **Air Infiltration Seals**, which exceed the ASHRAE 90.1 Standard when installed with standard bottom seal and commonly available rigid/flexible vinyl door stop.

OPTIONS

2000 Series Available Options

- 2" or 3" Track
- Double Steel End Stiles
- Exhaust Port
- Cam Safety Device
- Spring Bumpers
- Chain Hoist
- Operators
- High Cycle Springs

- Glazing (lites)
- High Cycle Rollers
- Aluminum Full View Section
- Pass Door
- Keyed Lock
- Wind Load Rating
- ASTM E 84 Fire Rated

Optional Exhaust Port (interior view)



Pass Door (interior view)



(Convenience only, not a legal exit, or ADA compliant. Door trim color is only available in clear anodized. Available in doors up to 16'2" wide, 16' high. Not available in all models.)

For detailed information about the construction of this series, see pages 34-35.

Model	Door Thickness	Tested U-Factor	Max. Door Size		End Stile Type	Section Skins	
			Width	Height		Inside	Outside
2010	2" (50.8mm)	0.094	18'-2"	16'-0"	Extruded End Cap	26 GA V-Groove Woodgrain Steel	26 GA Flush Woodgrain Steel
2012	2" (50.8mm)	0.094	18'-2"	16'-0"	Extruded End Cap	26 GA V-Groove Woodgrain Steel	26 GA V-Groove Woodgrain Steel
2014	2" (50.8mm)	0.094	38'-2"	32'-0"	16 GA Steel	26 GA V-Groove Woodgrain Steel	26 GA Flush Woodgrain Steel
2016	2" (50.8mm)	0.094	38'-2"	32'-0"	16 GA Steel	26 GA V-Groove Woodgrain Steel	26 GA V-Groove Woodgrain Steel
2032	2" (50.8mm)	0.094	24'-2"	32'-0"	16 GA Steel	26 GA V-Groove Woodgrain Steel	20 GA Flush Smooth Steel
2033	2" (50.8mm)	0.094	38'-2"	32'-0"	16 GA Steel	26 GA V-Groove Woodgrain Steel	20 GA V-Groove Smooth Steel
2032-20	2" (50.8mm)	0.094	24'-2"	32'-0"	16 GA Steel	20 GA V-Groove Smooth Steel	20 GA Flush Smooth Steel
2033-20	2" (50.8mm)	0.094	38'-2"	32'-0"	16 GA Steel	20 GA V-Groove Smooth Steel	20 GA V-Groove Smooth Steel
2060, 2072, 2082	2" (50.8mm)	0.094	24'-2"	32'-0"	Extruded End Cap	26 GA V-Groove Woodgrain Steel	26 GA Ribbed Short Panel Woodgrain Steel
2061, 2071, 2081	2" (50.8mm)	0.094	24'-2"	32'-0"	Extruded End Cap	26 GA V-Groove Woodgrain Steel	26 GA Recessed Short Panel Woodgrain Steel
2063, 2073	2" (50.8mm)	0.094	18'-2"	16'-0"	Extruded End Cap	26 GA V-Groove Woodgrain Steel	26 GA Recessed Long Panel Woodgrain Steel
2064, 2074	2" (50.8mm)	0.094	18'-2"	16'-0"	Extruded End Cap	26 GA V-Groove Woodgrain Steel	26 GA Ribbed Long Panel Woodgrain Steel
2067, 2070, 2087	2" (50.8mm)	0.094	24'-2"	32'-0"	Extruded End Cap	26 GA V-Groove Woodgrain Steel	26 GA Ranch Panel Woodgrain Steel
2068, 2078, 2080	2" (50.8mm)	0.094	24'-2"	32'-0"	Extruded End Cap	26 GA V-Groove Woodgrain Steel	26 GA Standard Panel Woodgrain Steel
2069, 2079, 2090	2" (50.8mm)	0.094	24'-2"	32'-0"	Extruded End Cap	26 GA V-Groove Woodgrain Steel	26 GA Sculptured Panel Woodgrain Steel

Note: Certain weights and/or applications may limit the size allowed





716 in sandstone with full view sections

COMMERCIAL 700 SERIES

1 3/4" Thick



710 / 712 / 714 / 716 / 732 / 733 /
732-20 / 733-20 / 760 / 763 / 764 /
767 / 768 / 769 / 770 / 771 / 772 /
773 / 774 / 778 / 779 / 780 / 781 /
782 / 787 / 790



700

Built to Last

Haas 700 Series commercial insulated steel doors stand up to the elements, while dramatically decreasing exterior noise and enhancing the overall aesthetics of your building at the same time. The 1 3/4" thick 700 Series insulated steel doors help increase energy savings with polyurethane foam cores and are built to last.



716 in polar white with large TL lites



716 in charcoal with large TL lites

INSULATED




700 DOOR PANELS



Flush Woodgrain
All colors except Bi-Directionals
Model 710 Window Options: p 42-45
Model 714 Window Options: p 45

V-Groove Woodgrain
All colors except Bi-Directionals
Model 712 Window Options: p 44-45
Model 716 Window Options: p 45


Flush Smooth
Polar White and Brown
Model 732 Window Options: p 45
Model 732-20 Window Options: p 45




V-Groove Smooth
Polar White and Brown
Model 733 Window Options: p 45
Model 733-20 Window Options: p 45




Ribbed Short Woodgrain Panel
All colors except Bi-Directional
American Walnut for 772 and 782
Model 760 Window Options: p 43
Model 772 Window Options: p 44
Model 782 Window Options: p 42




Recessed Short Woodgrain Panel
All colors except Bi-Directional
American Walnut for 771 and 781
Model 761 Window Options: p 43
Model 771 Window Options: p 44
Model 781 Window Options: p 42




Ribbed Long Woodgrain Panel
All colors except Bi-Directional
American Walnut for 774
Model 764 Window Options: p 43
Model 774 Window Options: p 44



Recessed Long Woodgrain Panel
All colors except Bi-Directional
American Walnut for 773
Model 763 Window Options: p 43
Model 773 Window Options: p 44




Raised Ranch Woodgrain Panel
All colors except Bi-Directional
American Walnut
Model 770 Window Options: p 44
Model 767 Window Options: p 43
Model 787 Window Options: p 42



Raised Standard Woodgrain Panel
All colors except Bi-Directional
American Walnut
Model 780 Window Options: p 42
Model 768 Window Options: p 43
Model 778 Window Options: p 44



Raised Sculptured Woodgrain Panel
All colors except Bi-Directional
American Walnut
Model 790 Window Options: p 42
Model 769 Window Options: p 43
Model 779 Window Options: p 44



A **Full Thermal Break** is used in the tongue-and-groove construction of all 700 series doors. This rigid vinyl extrusion seals the joints and eliminates metal-to-metal contact, which limits the transfer of temperature.

700 QUICK GUIDE

Model	Door Thickness	Tested U-Factor	Max. Door Size		End Style Type	Section Skins	
			Width	Height		Inside	Outside
710	1-3/4" (44.5mm)	0.093	18'-2"	16'-0"	Extruded End Cap	26 GA V-Groove Woodgrain Steel	26 GA Flush Woodgrain Steel
712	1-3/4" (44.5mm)	0.093	18'-2"	16'-0"	Extruded End Cap	26 GA V-Groove Woodgrain Steel	26 GA V-Groove Woodgrain Steel
714	1-3/4" (44.5mm)	0.093	38'-2"	32'-0"	16 GA Steel	26 GA V-Groove Woodgrain Steel	26 GA Flush Woodgrain Steel
716	1-3/4" (44.5mm)	0.093	38'-2"	32'-0"	16 GA Steel	26 GA V-Groove Woodgrain Steel	26 GA V-Groove Woodgrain Steel
732	1-3/4" (44.5mm)	0.093	24'-2"	32'-0"	16 GA Steel	26 GA V-Groove Woodgrain Steel	20 GA Flush Smooth Steel
733	1-3/4" (44.5mm)	0.093	38'-2"	32'-0"	16 GA Steel	26 GA V-Groove Woodgrain Steel	20 GA V-Groove Smooth Steel
732-20	1-3/4" (44.5mm)	0.093	24'-2"	32'-0"	16 GA Steel	20 GA V-Groove Smooth Steel	20 GA Flush Smooth Steel
733-20	1-3/4" (44.5mm)	0.093	38'-2"	32'-0"	16 GA Steel	20 GA V-Groove Smooth Steel	20 GA V-Groove Smooth Steel
760, 772, 782	1-3/4" (44.5mm)	0.093	24'-2"	32'-0"	Extruded End Cap	26 GA V-Groove Woodgrain Steel	26 GA Ribbed Short Panel Woodgrain Steel
761, 771, 781	1-3/4" (44.5mm)	0.093	24'-2"	32'-0"	Extruded End Cap	26 GA V-Groove Woodgrain Steel	26 GA Recessed Short Panel Woodgrain Steel
763, 773	1-3/4" (44.5mm)	0.093	18'-2"	16'-0"	Extruded End Cap	26 GA V-Groove Woodgrain Steel	26 GA Recessed Long Panel Woodgrain Steel
764, 774	1-3/4" (44.5mm)	0.093	18'-2"	16'-0"	Extruded End Cap	26 GA V-Groove Woodgrain Steel	26 GA Ribbed Long Panel Woodgrain Steel
767, 770, 787	1-3/4" (44.5mm)	0.093	24'-2"	32'-0"	Extruded End Cap	26 GA V-Groove Woodgrain Steel	26 GA Ranch Panel Woodgrain Steel
768, 778, 780	1-3/4" (44.5mm)	0.093	24'-2"	32'-0"	Extruded End Cap	26 GA V-Groove Woodgrain Steel	26 GA Standard Panel Woodgrain Steel
769, 779, 790	1-3/4" (44.5mm)	0.093	24'-2"	32'-0"	Extruded End Cap	26 GA V-Groove Woodgrain Steel	26 GA Sculptured Panel Woodgrain Steel

Note: Certain weights and/or applications may limit the size allowed

OPTIONS

- 700 Series Available Options**
- 2" or 3" Track
 - Double Steel End Stiles
 - Exhaust Port
 - Cam Safety Device
 - Spring Bumpers
 - Chain Hoist
 - Operators
 - High Cycle Springs
 - Glazing (lites)
 - High Cycle Rollers
 - Aluminum Full View Section
 - Pass Door
 - Top Header Seal
 - Keyed Lock
 - Wind Load Rating
 - ASTM E 84 Fire Rated

Optional Exhaust Port (interior view)



Pass Door (exterior view)



(Convenience only, not a legal exit, or ADA compliant. Door trim color is only available in clear anodized. Available in doors up to 16'2" wide, 16' high. Not available in all models.)



660 in polar white

COMMERCIAL 600 SERIES

1 3/8" Thick



610 / 612 / 614 / 616 / 632 / 632-20 /
633 / 633-20 / 660 / 661 / 663 / 664 /
667 / 668 / 669 / 670 / 671 / 672 /
673 / 674 / 678 / 679 / 680 / 681 /
682 / 687 / 690

Strong, Efficient and Attractive

When your major considerations include energy efficiency, noise buffering and beauty, a Haas 600 Series commercial insulated steel door will far exceed your expectations. These environmentally compliant, polyurethane foam-injected steel doors offer exceptional benefits for commercial applications, including durable strength, unique paint system and hard working hardware to withstand the harshest of elements.

INSULATED



616 in sandstone



614 in charcoal with large TL lites



612 in polar white with small TL lites


600 QUICK GUIDE

Model	Door Thickness	Tested U-Factor	Max. Door Size		End Style Type	Section Skins	
			Width	Height		Inside	Outside
✓ 610	1-3/8" (34.9mm)	0.106	18'-2"	16'-0"	Extruded End Cap	26 GA V-Groove Woodgrain Steel	26 GA Flush Woodgrain Steel
✓ 612	1-3/8" (34.9mm)	0.106	18'-2"	16'-0"	Extruded End Cap	26 GA V-Groove Woodgrain Steel	26 GA V-Groove Woodgrain Steel
✓ 614	1-3/8" (34.9mm)	0.106	18'-2"	16'-0"	16 GA Steel	26 GA V-Groove Woodgrain Steel	26 GA Flush Woodgrain Steel
✓ 616	1-3/8" (34.9mm)	0.106	18'-2"	16'-0"	16 GA Steel	26 GA V-Groove Woodgrain Steel	26 GA V-Groove Woodgrain Steel
✓ 632	1-3/8" (34.9mm)	0.106	18'-2"	16'-0"	16 GA Steel	26 GA V-Groove Woodgrain Steel	20 GA Flush Smooth Steel
✓ 633	1-3/8" (34.9mm)	0.106	18'-2"	16'-0"	16 GA Steel	26 GA V-Groove Woodgrain Steel	20 GA V-Groove Smooth Steel
✓ 632-20	1-3/8" (34.9mm)	0.106	18'-2"	16'-0"	16 GA Steel	20 GA V-Groove Smooth Steel	20 GA Flush Smooth Steel
✓ 633-20	1-3/8" (34.9mm)	0.106	18'-2"	16'-0"	16 GA Steel	20 GA V-Groove Smooth Steel	20 GA V-Groove Smooth Steel
✓ 660, 672, 682	1-3/8" (34.9mm)	0.106	18'-2"	16'-0"	Extruded End Cap	26 GA V-Groove Woodgrain Steel	26 GA Ribbed Short Panel Woodgrain Steel
✓ 661, 671, 681	1-3/8" (34.9mm)	0.106	18'-2"	16'-0"	Extruded End Cap	26 GA V-Groove Woodgrain Steel	26 GA Recessed Short Panel Woodgrain Steel
✓ 663, 673	1-3/8" (34.9mm)	0.106	18'-2"	16'-0"	Extruded End Cap	26 GA V-Groove Woodgrain Steel	26 GA Recessed Long Panel Woodgrain Steel
✓ 664, 674	1-3/8" (34.9mm)	0.106	18'-2"	16'-0"	Extruded End Cap	26 GA V-Groove Woodgrain Steel	26 GA Ribbed Long Panel Woodgrain Steel
✓ 667, 670, 687	1-3/8" (34.9mm)	0.106	18'-2"	16'-0"	Extruded End Cap	26 GA V-Groove Woodgrain Steel	26 GA Ranch Panel Woodgrain Steel
✓ 668, 678, 680	1-3/8" (34.9mm)	0.106	18'-2"	16'-0"	Extruded End Cap	26 GA V-Groove Woodgrain Steel	26 GA Standard Panel Woodgrain Steel
✓ 669, 679, 690	1-3/8" (34.9mm)	0.106	18'-2"	16'-0"	Extruded End Cap	26 GA V-Groove Woodgrain Steel	26 GA Sculptured Panel Woodgrain Steel


DOOR PANELS




Flush Woodgrain
All colors except Bi-Directionals
Model 610 Window Options: p 42-45
Model 614 Window Options: p 45



V-Groove Woodgrain
All colors except Bi-Directionals
Model 612 Window Options: p 44-45
Model 616 Window Options: p 45




Flush Smooth
Polar White and Brown
Model 632 Window Options: p 45
Model 632-20 Window Options: p 45



V-Groove Smooth
Polar White and Brown
Model 633 Window Options: p 45
Model 633-20 Window Options: p 45




Ribbed Short Woodgrain Panel
All colors except Bi-Directional
American Walnut for 672 and 682
Model 660 Window Options: p 43
Model 672 Window Options: p 44
Model 682 Window Options: p 42



Recessed Short Woodgrain Panel
All colors except Bi-Directional
American Walnut for 671 and 681
Model 661 Window Options: p 44
Model 671 Window Options: p 44
Model 681 Window Options: p 42



Recessed Long Woodgrain Panel
All colors except Bi-Directional
American Walnut for 673
Model 663 Window Options: p 43
Model 673 Window Options: p 44



Ribbed Long Woodgrain Panel
All colors except Bi-Directional
American Walnut for 674
Model 664 Window Options: p 43
Model 674 Window Options: p 44




Raised Ranch Woodgrain Panel
All colors except Bi-Directional
American Walnut
Model 670 Window Options: p 44
Model 667 Window Options: p 43
Model 687 Window Options: p 42



Raised Standard Woodgrain Panel
All colors except Bi-Directional
American Walnut
Model 680 Window Options: p 42
Model 668 Window Options: p 43
Model 678 Window Options: p 44



Sculptured Raised Woodgrain Panel
All colors except Bi-Directional
American Walnut
Model 690 Window Options: p 42
Model 669 Window Options: p 43
Model 679 Window Options: p 44



A **Full Thermal Break** is used in the tongue-and-groove construction of all 600 series doors. This rigid vinyl extrusion seals the joints and eliminates metal-to-metal contact, which limits the transfer of temperature.

600 series doors exceed the ASHRAE 90.1 Standard when installed with standard bottom seal and commonly available rigid/flexible vinyl door stop.

OPTIONS

600 Series Available Options

- 2" or 3" Track
- Double Steel End Stiles
- Exhaust Port
- Cam Safety Device
- Spring Bumpers
- Chain Hoist
- Operators
- High Cycle Springs
- Glazing (lites)
- High Cycle Rollers
- Keyed Lock
- Wind Load Rating
- ASTM E 84 Fire Rated

Optional Exhaust Port (interior view)



For detailed information about the construction of this series, see pages 34-35.



C2415 in brown

COMMERCIAL RIBBED STEEL

2" Thick Optional Insulation

C2011 / C2011L / C2011S / C2015 / C2015L / C2015S / C2410 / C2410L / C2411 / C2411L / C2411S / C2415 / C2415L / C2415S / C2460 / C2460L / C2461 / C2461L / C2470 / C2470L / C2471 / C2471L / C2472 / C2472L / C2480 / C2480L / C2480S / C2481 / C2481L / C2482 / C2482L / C2511 / C2511L / C2511S



Strength and Value

The Haas Commercial Ribbed Steel Series doors are a value-based product that offers the strength of steel in four panel styles and five color choices. All models offer the upgrade of adding energy-efficient insulation panels. Ribbed steel doors are the ideal choice when economy is the prime consideration but a high quality, beautifully crafted product is still a necessity.

Ribbed Steel / 2" thick / optional insulation



C2015 in polar white



C2011 in polar white with full view section



C2511 in polar white with large lites



C2411 in sandstone

Model	Door Thickness	Tested U-Factor	Max. Door Size		End Stile Type	Section Skins		Insulation Type	Stile GA
			Width	Height		Inside	Outside		
C2011	2"	N/A	30'-2"	20'-0"	C-Shaped Steel	N/A	20 GA Ribbed Steel	None	18
C2011L	2"	N/A	30'-2"	20'-0"	C-Shaped Steel	Laminate Backer	20 GA Ribbed Steel	Inserted Polystyrene Panels	18
C2011S	2"	N/A	24'-2"	20'-0"	C-Shaped Steel	Steel Backer	20 GA Ribbed Steel	Inserted Polystyrene Panels	18
C2015	2"	N/A	30'-2"	20'-0"	C-Shaped Steel	N/A	20 GA Ribbed Steel	None	16
C2015L	2"	N/A	30'-2"	20'-0"	C-Shaped Steel	Laminate Backer	20 GA Ribbed Steel	Inserted Polystyrene Panels	16
C2015S	2"	N/A	24'-2"	20'-0"	C-Shaped Steel	Steel Backer	20 GA Ribbed Steel	Inserted Polystyrene Panels	16
C2411**	2"	N/A	30'-2"	20'-0"	C-Shaped Steel	N/A	24 GA Ribbed Steel	None	18
C2411L**	2"	N/A	30'-2"	20'-0"	C-Shaped Steel	Laminate Backer	24 GA Ribbed Steel	Inserted Polystyrene Panels	18
C2411S	2"	N/A	24'-2"	20'-0"	C-Shaped Steel	Steel Backer	24 GA Ribbed Steel	Inserted Polystyrene Panels	18
C2415**	2"	N/A	30'-2"	20'-0"	C-Shaped Steel	N/A	24 GA Ribbed Steel	None	16
C2415L**	2"	N/A	30'-2"	20'-0"	C-Shaped Steel	Laminate Backer	24 GA Ribbed Steel	Inserted Polystyrene Panels	16
C2415S	2"	N/A	24'-2"	20'-0"	C-Shaped Steel	Steel Backer	24 GA Ribbed Steel	Inserted Polystyrene Panels	16
C2511	2"	N/A	16'-2"	16'-0"	C-Shaped Steel	N/A	24 GA Nominal Ribbed Steel	None	18
C2511L	2"	N/A	16'-2"	16'-0"	C-Shaped Steel	Laminate Backer	24 GA Nominal Ribbed Steel	Inserted Polystyrene Panels	18
C2511S	2"	N/A	16'-2"	16'-0"	C-Shaped Steel	Steel Backer	24 GA Nominal Ribbed Steel	Inserted Polystyrene Panels	18
C2410	2"	N/A	18'-2"	10'-0"	C-Shaped Steel	N/A	24 GA Flush Panel Woodgrain Steel	None	18
✓ C2410L	2"	0.215	18'-2"	10'-0"	C-Shaped Steel	Laminate Backer	24 GA Flush Panel Woodgrain Steel	Inserted Polystyrene Panels	18
C2470	2"	N/A	24'-2"	16'-0"	C-Shaped Steel	N/A	24 GA Ranch Panel Woodgrain Steel	None	18
✓ C2470L	2"	0.215	24'-2"	16'-0"	C-Shaped Steel	Laminate Backer	24 GA Ranch Panel Woodgrain Steel	Inserted Polystyrene Panels	18
C2480	2"	N/A	24'-2"	16'-0"	C-Shaped Steel	N/A	24 GA Standard Panel Woodgrain Steel	None	18
✓ C2480L	2"	0.215	24'-2"	16'-0"	C-Shaped Steel	Laminate Backer	24 GA Standard Panel Woodgrain Steel	Inserted Polystyrene Panels	18
✓ C2480S	2"	0.225	24'-2"	16'-0"	C-Shaped Steel	Steel Backer	24 GA Standard Panel Woodgrain Steel	Inserted Polystyrene Panels	18
C2460, C2472, C2482	2"	N/A	24'-2"	16'-0"	C-Shaped Steel	N/A	24 GA Ribbed Short Panel Woodgrain Steel	None	18
✓ C2460L, C2472L, C2482L	2"	0.215	24'-2"	16'-0"	C-Shaped Steel	Laminate Backer	24 GA Ribbed Short Panel Woodgrain Steel	Inserted Polystyrene Panels	18
C2461, C2471, C2481	2"	N/A	24'-2"	16'-0"	C-Shaped Steel	N/A	24 GA Recessed Short Steel	None	18
✓ C2461L, C2471L, C2481L	2"	0.215	24'-2"	16'-0"	C-Shaped Steel	Laminate Backer	24 GA Recessed Short Steel	Inserted Polystyrene Panels	18

**widths over 24' 2" are only available in polar white

DOOR PANELS



Smooth Ribbed Steel

Polar White Only
Models C2011, C2011L, C2011S, C2015, C2015L, C2015S, C2511, C2511L, C2511S
 Window Options: p 45
 Polar White, Sandstone & Brown
Models C2411, C2411L, C2411S, C2415, C2415L, C2415S
 Window Options: p 45




Flush Woodgrain

Polar White, Almond, Sahara Tan, Sandstone, Brown, Charcoal & English Oak
Models C2410, C2410L
 Window Options: p 42-45



Ribbed Short Woodgrain Panel

Polar White, Almond, Sahara Tan, Sandstone, Brown, Charcoal & English Oak
 (not available in 18" sections)
Models C2460, C2460L
 Window Options: p 43
Models C2472, C2472L
 Window Options: p 44
Models C2482, C2482L
 Window Options: p 42



Recessed Short Woodgrain Panel

Polar White, Almond, Sahara Tan, Sandstone, Brown, Charcoal & English Oak
 (not available in 18" sections)
Models C2461, C2461L
 Window Options: p 43
Models C2471, C2471L
 Window Options: p 44
Models C2481, C2481L
 Window Options: p 42



Raised Ranch Woodgrain Panel

Polar White, Almond, Sahara Tan, Sandstone, Brown, Charcoal & English Oak
Models C2470, C2470L
 Window Options: p 44



Raised Standard Woodgrain Panel

Polar White, Almond, Sahara Tan, Sandstone, Brown, Charcoal & English Oak
Models C2480, C2480L, C2480S
 Window Options: p 42

OPTIONS

Ribbed Steel Available Options

- 2" or 3" Track
- Double Steel End Stiles
- Exhaust Port
- Cam Safety Device
- Spring Bumpers
- Chain Hoist
- Operators
- High Cycle Springs
- Glazing (lites)
- High Cycle Rollers
- Aluminum Full View Section
- Keyed Lock
- Wind Load Rating
- Impact Lites on some Models



Bottom Seal



Non-Insulated - inside view




Insulated Laminate Back (L) - inside view



Optional Exhaust Port (interior view)



Insulated Steel Back (S) - inside view



Ribbed Steel / 2" thick / optional insulation

The Strength To Keep Out Noise And Weather

Haas commercial insulated doors stand up to the elements, while dramatically decreasing exterior noise and enhancing the overall aesthetics of your building at the same time. Choosing one of our insulated doors will help increase energy savings, as our environmentally compliant polyurethane provides one of the best U-Factors available in sectional doors.

Haas garage doors are made from steel that contains 80% recycled material. They are reinforced with roll-formed galvanized steel struts and double-end hinges, as required to meet wind load specifications and to comply with ANSI/DASMA 102. The protective coating system is found on both the interior and exterior steel.

Environmentally Compliant Polyurethane Foam Construction

The polyurethane foam in a Haas garage door section is fully enclosed inside the steel skins. This design puts the insulation properties of polyurethane foam far ahead of polystyrene foam for performance and value.

Polyurethane foam is a two-part system. It begins with two chemical blends that when mixed together expand and cure to fill the garage door panel. During the expansion, the foam completely fills the inside of the panel and becomes fully adhered to the steel skins of the garage door panel to form a composite structure that is of exceptional strength and rigidity. Polyurethane foams are very stable when encapsulated inside a garage door section.

Insulating with polyurethane provides a superior product with higher insulation properties and a stronger unitized section.

Commercial Insulated Quick Reference

Series	Thickness	Tested U-Factor
9200	2" & 5/8" overlay	0.081
9600	1-3/8" & 5/8" overlay	0.096
5800	3"	0.089
5200	2"	0.110
5700	1-3/4"	0.097
800	3"	0.089
2000	2"	0.094
700	1-3/4"	0.093
600	1-3/8"	0.106

Air Infiltration Seal

5800, 5200, 800 and 2000 series doors include Air Infiltration Seals, which exceed the ASHRAE 90.1 Standard when installed with standard bottom seal and commonly available rigid/flexible vinyl door stop.

Full Thermal Break

A full Thermal Break is used in the tongue-and-groove construction of all commercial insulated doors. This rigid vinyl extrusion seals the joints and eliminates metal-to-metal contact between door sections, which limits the transfer of temperature. This also provides optimum water and wind resistance.

Weather Seal

A full-length, one-piece heavy vinyl bottom weather seal prevents infiltration of air, rain, snow and debris. The seal reduces impact shocks when the door is closed against concrete flooring.



Unique Paint System

All Haas steel garage doors include a three-tier, corrosion-resistant protective paint system with a polyurethane primer and durable polyester finish coat on the interior and exterior. Haas Door's paint thickness is one of the highest in the industry, and most insulated door models are available in 19 colors.



Hard Working Hardware

Haas track is 2" or 3" galvanized steel, depending on door size, with bracket mount for wood jambs or continuous reverse mounting for steel jambs. For angle-mount track, door widths are 2" wider than the opening. Track rollers are 2" or 3" case-hardened inner and outer steel races with 10-ball pre-lubricated bearings. Hinges, brackets, and reinforcing struts are hot-dipped galvanized steel. Fasteners are plated for maximum corrosion resistance. Counterbalancing springs are torsion type, computer calibrated to match door load. This provides a 10,000-cycle life at the minimum; optional spring wires can achieve 25,000, 50,000 and 100,000 cycle requirements. Springs are wound from oil-tempered wire and mounted on a continuous cross header tube or solid shaft, as determined by torque load.



Contact one of our professional dealers for information on additional options including: exterior cylinder locks, chain hoist operation, safety bottom brackets, and special lift clearance tracks (high lift, vertical lift, low headroom, and those that follow the roof line).



Full View

Optional Aluminum Full View sections on the 5000 Series, 2000 Series, 700 Series and Commercial Ribbed Steel provide maximum light and visibility with available insulated glazing. Full view sections for the 5000 Series are available in polar white. Full view sections for the 2000 & 700 Series are available in 8 colors. Full view sections for Commercial Ribbed Steel are available in 5 colors. (Not available in Wood Grain colors.)



The E-Strut® and Wind Load

The E-Strut is the next generation of strut design. Conceived, developed and manufactured by Haas Door, testing has proven the E-Strut to outperform traditional struts. This patented design is used on all Haas Door products.

The innovative E-Strut is intelligently designed to require half as many tek screws as u-bars and struts currently in use. This means less time attaching struts in the field for installers and a savings in labor expense for our dealers.

E-Struts are available in 2 inch, 3 inch, 4 inch and 6 inch widths and come standard in a galvanized finish. The 4 inch and 6 inch sizes do not require hinge straps.

Haas Door products are available in a wide range of design pressures for wind load requirements. Contact your local Haas Door dealer for more information about wind load requirements in your area.



Pass Door

Custom pass doors are also available on the 2000 & 700 Series.


THERMAL PERFORMANCE U-FACTOR

What is U-Factor?

The tested U-Factor is the measurement of heat (energy) transfer from warmer side to colder side of the garage door (in our case). Heat transfer is not desired because it means the loss of energy from conditioned spaces.

A lower U-Factor indicates less heat transfer and better thermal performance.

It is the preferred method for building codes thermal performance, and architects use U-Factors to calculate building envelope energy loads. U-Factor tests the whole, installed assembly. Energy Star Fenestration products and knowledgeable professionals recognize and use U-Factor.




Without insulation or thermal break to stop it, energy will transfer through the door.

Who is requesting this industry standard?

Door & Access Systems Manufacturers Association (DASMA) has setup a verification program to provide industry wide standardization of marketing the thermal performance of sectional garage doors. This program represents a shift in how sectional garage doors thermal performance is rated, from traditional R-Value to more accurate and relevant 3rd party tested door assembly U-Factor.

DASMA and the program participants agree to increased consistency, and transparency by sharing tested data, allowing customers to compare product quality facts. More detailed information about the program and U-Factors are available at www.dasma.com/thermal.



Why is a tested U-Factor better than a calculated R-Value?

Tested U-Factor

- U-Factor tests the whole installed assembly which includes section joint, lites, stile attachment, etc. - more relevant to thermal performance
- Third party tested and validated by the program administrator
- All manufacturers using the same testing methods ANSI/DASMA 105
- Tests measure the actual heat/energy transfer
- All manufacturer results will be a direct comparison to one another

Calculated R-Value

- Only one section is calculated and provides the insulating effect through the "center" of a door section only, not the entire door
- Independently calculated by each manufacturer - not validated
- No testing standard resulting in a wide interpretation of the calculation
- Calculates the resistance to thermal transfer

How does this benefit you?

This shift to tested U-Factor measurements sets a standard all manufacturers in the program adhere to. Tested products included in the program must be submitted to the program administrator. Only tested products in the program can list U-Factor data. This is the most reliable thermal performance indicator in the industry. Manufacturers in the program are stepping forward and formally having their products tested to prove quality.

Comparison of products between manufacturers has never been easier or more accurate. All tested products are required to be labeled with DASMA thermal performance verification displaying testing results. For accurate data and product comparison, choose products that have been tested through this program.

Establishing the standard testing procedure, and having a third party accredited lab perform and record the testing data provides consistency across the industry. Special guidelines have been put in place to properly market the U-Factor information as well. This removes any possible confusion from one manufacturer to another.

How can I tell if the product has been tested?


The use of DASMA thermal performance Badge, Label, or Icon will quickly identify products included in the program.



Badge



Icon



Label

American Tradition™ 9000 Series

- 10 Year Delamination and Rust-through Warranty on Sections
- 10 Year Finish Warranty
- 5 Year Overlay Delamination
- 1 Year Hardware Warranty
- 1 Year Spring Warranty
- 1 Year All Other Components

Commercial Aluminum Series

- 1 Year Hardware Warranty
- 1 Year Finish Warranty
- 1 Year Spring Warranty
- 1 Year All Other Components

Insulated Aluminum 5000 Series


- 10 Year Delamination Warranty
- 10 Year Finish Warranty
- 1 Year Hardware Warranty
- 1 Year Spring Warranty
- 1 Year All Other Components

Insulated Steel - 800, 2000, 700 & 600 Series

- 10 Year Delamination and Rust-through Warranty
- 10 Year Finish Warranty
- 1 Year Hardware Warranty
- 1 Year Spring Warranty
- 1 Year All Other Components

Ribbed Steel - 2400 & 2500 Series

- 1 Year Rust-through Warranty
- 1 Year Hardware Warranty
- 1 Year Spring Warranty
- 1 Year All Other Components



www.haasdoor.com/commercial

www.haasdoor.com/architects




3 Part Specification/BIM

www.haasdoor.com/specs

1/8" Non-Insulated




1/4" Non-Insulated (Only Commercial Aluminum)



1/2" Insulated



Impact Polycarbonate (UV rating on Clear only)




SELECTVIEW OPTIONS

SelectView allows you to select unique window placements based on the door series and window. SelectView is unique due to the vast amount of options available to suit any need. Whether you're looking to add some character to a ribbed steel commercial building project, or adding more lite into a warehouse renovation, SelectView provides many options to give your project differentiation.

- Available in 800, 2000, 700, 600 and Ribbed Steel* Series
- Multiple window placement options by series and panel styles
- Ranch and Standard Series windows use their matching panel, Carriage House Series windows use Flush panels, and TL lites available in Flush, V-Groove, and Ribbed Steel*
- Available with Specialty Glass and insert options


- Insulated and Non-insulated glass options in Carriage House, Ranch, Standard, and TL lites
- Standard and Wood Grain color options follow door Series
- Max size 18'2" x 16' - More than one lite in the bottom section is limited to 18'2" x 10'0"

*Ribbed Steel Series are limited to 1 window in bottom section



Carriage House Options

- Add windows to a flush door to create a modern, custom look to fit the style of your building.
- Available in Flush panel models.
- Available with Decorative glass, Specialty glass & inserts.
- Largest glass window size - 39 7/16" x 13 5/8".




TL Options

- Take the ordinary residential or commercial door to extraordinary.
- Available in Flush, V-Groove, and Ribbed Steel* models.
- Available with Clear or Frosted glass.
- Commercial Ribbed Steel: 24" x 6" & 24" x 12" window sizes, black frame – All other series: 25" x 12" & 24" x 6" window sizes, large window frame matches door color.




(Possibilities shown above, many more available)



Standard Options

- Mix windows & standard panels for a unique look.
- Available in Raised Standard stamped panel models.
- Available with Decorative glass, Specialty glass & inserts.
- 18 3/8" x 11 3/8" window size for 800, 2000, 700 & 600 Series – 17 3/8" x 11 3/8" window size for 2400, 2500 & Commercial Ribbed Steel* Series.
- 2400 Series are limited to 1 lite in bottom section.



Ranch Options

- Create curb appeal with windows & panels.
- Available in Raised Ranch stamped panel models.
- Available with Decorative glass, Specialty glass & inserts.
- 39 3/8" x 11 1/2" size window.

(Possibilities shown above, many more available)

Standard Series

Models 610, 680, 681, 682, 687, 690,
710, 780, 781, 782, 787, 790, 5710,
5780, 5787
1/8" DSB, 1/8" Tempered
1/2" Insulated Tempered

Models 2010, 2080, 2081, 2082,
2087, 2090, 5210, 5280, 5287
1/2" Insulated

Models C2410, C2410L, C2480, C2480S,
C2480L, C2481, C2481L, C2482, C2482L
1/8" DSB, 1/8" Tempered

Cascade



Cathedral



Colonial



Plain



Prairie



Sherwood



Carriage House Series (not available in 18" sections)

Models 610, 660, 661, 663, 664, 667,
668, 669, 710, 760, 761, 763, 764,
767, 768, 769, 5710, 5767, 5768
1/8" Tempered
1/2" Insulated Tempered

Models 2010, 2060, 2061, 2063, 2064,
2067, 2068, 2069, 5210, 5267, 5268
3/4" Insulated Tempered

Models C2410, C2410L,
C2460, C2460L, C2461, C2461L
1/8" Tempered

3-Pane



3-Pane
Single Arch



3-Pane
Double Arch



4-Pane



4-Pane
Single Arch



4-Pane
Double Arch



6-Pane



6-Pane
Single Arch



6-Pane
Double Arch



8-Pane



8-Pane
Single Arch



8-Pane
Double Arch



Plain



Ranch Series

Models 610, 670, 671, 672, 673, 674, 678, 679, 710, 770, 771, 772, 773, 774, 778, 779, 5710, 5770, 5778
1/8" Tempered
1/2" Insulated Tempered

Models 2010, 2070, 2071, 2072, 2073, 2074, 2078, 2079, 5210, 5270, 5278
1/2" Insulated Tempered

Models C2410, C2410L, C2470, C2470L, C2471, C2471L, C2472, C2472L
1/8" Tempered



SlimLine

Models 710, 712, 5710, 5712
7/8" Insulated Tempered

Models 610, 612, 2010, 2012, 5210, 5212
1/2" Insulated Tempered



TL Lites

Models 610, 612, 614, 616, 632, 633, 710, 712, 714, 716, 732, 732-20, 733, 733-20, 750, 751, 5710, 5712, 5714, 5716
1/2" Insulated Tempered - Clear or Frosted

Models 2010, 2012, 2014, 2016, 2032, 2032-20, 2033, 2033-20, 2050, 2051, 5210, 5212, 5214, 5216
3/4" Insulated Tempered - Clear or Frosted

Models 814, 816, 832, 832-20, 833, 833-20, 850, 851, 5814, 5816
1 3/4" Insulated Tempered - Clear or Frosted and Obscure for 25" x 12"



TL Lite 25" x 12"
(24 7/8" x 10 7/8" viewable)
Outer frame matches door color,
White inside frame.



Small TL Lite 24" x 6"
(21 1/2" x 3 1/4" viewable)
Outer frame available in Black or
White. Inside frame only available
in White.

Commercial Ribbed Steel Lites

Models C2011, C2015, C2411, C2415, C2511, C2410
1/8" Tempered - Clear or Frosted

Models C2011L, C2011S, C2015L, C2015S, C2415L, C2415S, C2511L, C2511S, C2411L, C2411S, C2410L
3/4" Insulated Tempered - Clear or Frosted




24" x 6"
(21 1/2" x 3 1/4" viewable)
Outer frame available in Black or
White. Inside frame only available
in White.



24" x 12"
(21 1/2" x 9 1/2" viewable)
Outer frame available in Black or
White. Inside frame only available
in White. Not available for Model
C2410 or C2410L.

COLOR OPTIONS

Solid Steel Colors



Polar White



Almond



Sahara Tan



Sandstone



Brown*



Charcoal



Gray (not available 2400/2500)



Bronze (not available 2400/2500)




Espresso* (not available 2400/2500)



Carbon Black* (not available 2400/2500)
(Not available in all sizes.)

*These colors include a cool chemistry paint finish, but is not recommended for projects with extreme exposures to heat and sunlight.

Insulated Aluminum Color



Polar White

COLOR OPTIONS

Uni-Directional Wood Grain Colors (Only English Oak available in 2400 series. Not available in 2500 series.)



American Walnut
Wood Grain Embossed



English Oak
Wood Grain Embossed



Ash
Wood Grain Embossed



Mahogany
Wood Grain Embossed



Graywood
Wood Grain Embossed



Ash
Uni-Directional Pattern

- These authentic colors feature a wood grain pattern that runs horizontally to compliment any of our insulated steel models.
- The pre-painted wood grain finish is baked on to ensure a durable and long lasting door. Steel wood grain colors feature a 10 year finish warranty.
- Built with 26 gauge galvanized steel that features a wood grain embossment.
- Available in all insulated steel models.

Bi-Directional Wood Grain Colors (not available in 2400 & 2500 series)



American Walnut
Stucco Embossed
(only available with Carriage House lites)




English Oak
Stucco Embossed
(only available with Carriage House lites)



Ash
Stucco Embossed



Mahogany
Stucco Embossed



Ash
Bi-Directional Pattern

- A vertical wood grain pattern on the panel and stile contrasting with a horizontal pattern on the rails creates the appearance of a real wood door.
- The pre-painted wood grain finish is baked on to ensure a durable and long lasting door. Steel wood grain colors feature a 10 year finish warranty.
- Built with 26 gauge galvanized steel that features a light stucco embossment.
- Available in all insulated steel models with a stamped panel.

Color Availability Chart

Model	Panel Type	Lites	Solid Steel Colors													Insulated Aluminum Color	Uni-Directional Steel Wood Grain Colors					Bi-Directional Steel Wood Grain Colors					
			Polar White	Almond	Sahara Tan	Sandstone	Brown	Espresso	Gray	Bronze	Charcoal	Carbon Black	Polar White	American Walnut	English Oak	Mahogany	Ash	Graywood	American Walnut	English Oak	Mahogany	Ash					
Insulated Models	5210 5710	Stucco Flush	TL																								
	2010 710 610	Woodgrain Flush	All	•	•	•	•	•	•	•	•	•	•	•	•	•	•		•	•	•	•	•				
	5212 5712	Stucco V Groove																									
	2012 712 612	V Groove	TL	•	•	•	•	•	•	•	•	•	•	•	•	•	•		•	•	•	•	•				
	5814 5214 5714	Stucco Flush	TL	•	•	•	•	•	•	•	•	•	•	•	•	•	•		•	•	•	•	•				
	2014 714 614	Woodgrain Flush	TL	•	•	•	•	•	•	•	•	•	•	•	•	•	•		•	•	•	•	•				
	5816 5216 5716	Woodgrain Flush	TL	•	•	•	•	•	•	•	•	•	•	•	•	•	•		•	•	•	•	•				
	814	Stucco V Groove	TL																								
	2016 716 616	V Groove	TL	•	•	•	•	•	•	•	•	•	•	•	•	•	•		•	•	•	•	•				
	816	V Groove	TL	•	•	•	•	•	•	•	•	•	•	•	•	•	•		•	•	•	•	•				
	832 2032 732 632	Smooth Flush	TL	•	•	•	•	•	•	•	•	•	•	•	•	•	•										
	833 2033 733 633	Smooth V Groove	TL	•	•	•	•	•	•	•	•	•	•	•	•	•	•										
	2060 760 660	Ribbed Short	Carriage	•	•	•	•	•	•	•	•	•	•	•	•	•	•		•	•	•	•	•	•	•	•	•
	2061 761 661	Recessed Short	Carriage	•	•	•	•	•	•	•	•	•	•	•	•	•	•		•	•	•	•	•	•	•	•	•
	2063 763 663	Recessed Long	Carriage	•	•	•	•	•	•	•	•	•	•	•	•	•	•		•	•	•	•	•	•	•	•	•
	2064 764 664	Ribbed Long	Carriage	•	•	•	•	•	•	•	•	•	•	•	•	•	•		•	•	•	•	•	•	•	•	•
	2070 770 670	Raised Ranch	Ranch	•	•	•	•	•	•	•	•	•	•	•	•	•	•		•	•	•	•	•	•	•	•	•
	5870 5270 5770	Raised Ranch	Ranch																•	•	•	•	•				
	870	Raised Ranch	Ranch	•	•	•	•	•	•	•	•	•	•	•	•	•	•							•	•	•	•
	2071 771 671	Recessed Short	Ranch	•	•	•	•	•	•	•	•	•	•	•	•	•	•		•	•	•	•	•	•	•	•	•
2072 772 672	Ribbed Short	Ranch	•	•	•	•	•	•	•	•	•	•	•	•	•	•		•	•	•	•	•	•	•	•	•	
2073 773 673	Recessed Long	Ranch	•	•	•	•	•	•	•	•	•	•	•	•	•	•		•	•	•	•	•	•	•	•	•	
2074 774 674	Ribbed Long	Ranch	•	•	•	•	•	•	•	•	•	•	•	•	•	•		•	•	•	•	•	•	•	•	•	
2080 780 680	Raised Standard	Standard	•	•	•	•	•	•	•	•	•	•	•	•	•	•		•	•	•	•	•	•	•	•	•	
5880 5280 5780	Raised Standard	Standard																•	•	•	•	•					
880	Raised Standard	Standard	•	•	•	•	•	•	•	•	•	•	•	•	•	•							•	•	•	•	
2081 781 681	Recessed Short	Standard	•	•	•	•	•	•	•	•	•	•	•	•	•	•		•	•	•	•	•	•	•	•	•	
2082 782 682	Ribbed Short	Standard	•	•	•	•	•	•	•	•	•	•	•	•	•	•		•	•	•	•	•	•	•	•	•	
2090 790 690	Raised Sculptured	Standard	•	•	•	•	•	•	•	•	•	•	•	•	•	•		•	•	•	•	•	•	•	•	•	
890	Raised Sculptured	Standard	•	•	•	•	•	•	•	•	•	•	•	•	•	•		•	•	•	•	•	•	•	•	•	
9220 9221 9222 9240 9241 9242	WG Flush/Overlays	Carriage	•	•	•	•	•	•	•	•	•	•	•	•	•	•		•	•	•	•	•					
9230 9231 9232 9250 9251 9252	WG Flush/Overlays	Carriage	•	•	•	•	•	•	•	•	•	•	•	•	•	•		•	•	•	•	•					
9620 9621 9622 9640 9641 9642	WG Flush/Overlays	Carriage	•	•	•	•	•	•	•	•	•	•	•	•	•	•		•	•	•	•	•					
9630 9631 9632 9650 9651 9652	WG Flush/Overlays	Carriage	•	•	•	•	•	•	•	•	•	•	•	•	•	•		•	•	•	•	•					
Pan Models	C2011 C2015 C2511	Smooth Ribbed	Ribbed	•																							
	C2411 C2415	Smooth Ribbed	Ribbed	•																							
	C2410	Woodgrain Flush	All	•	•	•	•	•	•	•	•	•	•	•	•	•							•				
	C2460	Ribbed Short	Carriage	•	•	•	•	•	•	•	•	•	•	•	•	•							•				
	C2461	Recessed Short	Carriage	•	•	•	•	•	•	•	•	•	•	•	•	•							•				
	C2470	Raised Ranch	Ranch	•	•	•	•	•	•	•	•	•	•	•	•	•							•				
	C2471	Recessed Short	Ranch	•	•	•	•	•	•	•	•	•	•	•	•	•							•				
	C2472	Ribbed Short	Ranch	•	•	•	•	•	•	•	•	•	•	•	•	•							•				
	C2480	Raised Standard	Standard	•	•	•	•	•	•	•	•	•	•	•	•	•							•				
	C2481	Recessed Short	Standard	•	•	•	•	•	•	•	•	•	•	•	•	•							•				
C2482	Ribbed Short	Standard	•	•	•	•	•	•	•	•	•	•	•	•	•							•					

Haas Door is Committed to Quality.


As a member of the Door and Access Systems Manufacturers Association (DASMA), Haas Door is committed to industry standards for quality and safety. In addition to these guidelines, Haas Door has developed its own quality assurance procedures.

Each raw material used in the manufacturing process is inspected daily for quality assurance. Steel used on the inside and outside skins is checked for accuracy in thickness and finish. The insulation material, a high density environmentally compliant polyurethane foam, is tested continuously on each production line to ensure that the correct density, blend of material, cure time and tested U-Factors are achieved.

Samples of manufactured doors are tested for quality and durability. Doors are cycled tens of thousands of times to test the performance and endurance of the sections, hinges, springs, cables, rollers, bottom seals, and track. Strength is measured using two separate tests. Individual sections are subjected to a dead load test, and complete doors are wind load tested. This ensures that Haas garage doors will meet wind load requirements for building codes across the country.

Haas continues to perform testing outside of the manufacturing facility, as both prototype and current doors are installed in various locations and monitored for durability. External labs are also used to test specific components to ensure quality standards.

Quality people and quality products are what make Haas Door the best garage door manufacturer in the industry. Open the door to endless possibilities!



Environmental Responsibility

Haas Door Company manufactures all garage doors in the U.S. and is committed to providing quality products that are safe for our customers and to the environment. Haas garage doors are made from steel that contains 80% recycled material. A plastic thermal break, made with recycled materials, separates each door section to eliminate metal-to-metal contact and the transfer of temperature. Haas also uses environmentally compliant polyurethane insulation, which results in some of the most energy-efficient doors on the market. Good for the environment and saves energy!

Haas Door has also implemented an ongoing improvement plan to gain efficiency and reduce waste, including a recycling program for scrap metal, cardboard and plastic. Many suppliers are regional, which minimizes fuel costs, and material packaging is reused or recycled whenever possible.





Rev. 3.4
©Haas Door 2024

320 Sycamore
Wauseon, OH 43567

haasdoor.com



open the door to
endless possibilities